IF IT'S BROKEN, INCREDI-BOND CAN FIX IT!

MULTI-PURPOSE HIGH STRENGTH TWO COMPONENT BONDING AGENT FOR ALMOST ALL HOUSEHOLD MATERIALS INCLUDING WOOD, STEEL, CONCRETE, AND BRICK.

- Professional grade
- Works on damp surfaces including underwater
- Fill holes and cracked concrete
- Repair ceramic tile, glass and stucco
- Fasten block and brick
- 30 minute working time, 3 hour initial cure





EPOXY QUANTITY ESTIMATOR

CALCULATE HOW MUCH EPOXY YOUR JOB NEEDS

Quickly calculate the number of cartridges using the Epoxy
Quantity Estimator. Run our web application on your desktop,
smart phone or tablet from anywhere with an internet connection.





MITEK ANCHORING SOLUTIONS OFFER THE RIGHT FORMULA FOR ANY JOB!



CIA-EA Uncracked Concrete Epoxy Acrylate

High strength, fast cure structural adhesive for anchoring threaded rod and deformed rebar into uncracked concrete.

Code Evaluation Report: IAPMO ES ER-311



CIA-GEL 7000-C Cracked Concrete Epoxy

Attach anchor rods into concrete that may become cracked due to cyclic loading from earthquakes or wind.

Code Evaluation Report: IAPMO ES ER-473



CIA-GEL 7000 Masonry Epoxy

Specifically designed to attach anchor rods into fully grouted concrete masonry units. Evaluated for seismic, sustained load, elevated temperature and freeze-thaw suitability conditions.

Code Evaluation Report: ICC ES ESR-1702



CIA-GEL 6000-GP General Purpose Epoxy

Superior epoxy for general purpose structural applications that require quick load times and for doweling applications requiring state DOT approval.

Numerous DOT Approvals

To learn more about our Anchoring Solutions, visit our website at **MiTek-US.com** or call **800-328-5934** to place an order.